



Starting at \$2995
(U.S. list)

Zebra® 110XiIIIPlus™

High-Performance Bar Code Printer

Get high performance at a tremendous value.

Do you need a printer that can handle mission-critical, 24/7, heavy-industrial demands? With the new 110XiIIIPlus, you can step up to the renowned, non-stop reliability of Zebra's Xi™ printer family without a big leap in price. This new model with full four-inch print width comes in a choice of 203-, 300-, or 600-dpi resolution to fit your printing application, be it 4"x 6" compliance shipping labels, or tiny, sharply detailed labels for small components or products.

All the Plusses of an XiIIIPlus

Like every XiIIIPlus, it also offers a 32-bit processor for fast throughput, 16 MB SDRAM of onboard memory for fast "first-label-out" printing, and CompactFlash® for added label format/font storage—plus the most connectivity choices, including ZebraLink™ for remote printer management, ZebraNet® Wireless Card Socket, and USB 2.0, serial, and parallel ports. The 110XiIIIPlus can print reduced space symbology (RSS)—perfect for pharmaceutical companies wishing to comply with Federal Drug Administration (FDA) requirements for unit-of-use marking.

The 110XiIIIPlus integrates easily into a variety of industries and printing applications including:

- Life sciences—Small, high-resolution labels for vials and slides; unit-of-use labels for pharmaceutical products and packages; labels for surgical tools and diagnostic kits
- Electronics—Top- and bottom-side circuit board labeling; UL-Recognized/CSA-Accepted serial plate labels printed on demand
- Telecommunications—Product identification labels with company logos and Telecommunications Industry Forum required TLC39 stacked bar codes



Connect with it. Count on it.™

110XIIIPlus™



Specifications at a Glance*



The affordably priced 110XIIIPlus can handle your most extreme printing demands.

MAXIMUM PRINT AREA

Width:
203 dpi: 4.09"/104 mm
300 dpi: 4.09"/104 mm
600 dpi: 3.2"/81 mm
Length: 39"/991 mm

RESOLUTION

203 dpi/8 dots per mm
300 dpi/12 dots per mm
600 dpi/23.5 dots per mm

MAXIMUM PRINT SPEED

203 dpi: 10"/254 mm per second
300 dpi: 8"/203 mm per second
600 dpi: 4"/102 mm per second

MEMORY

16 MB SDRAM; 4 MB non-volatile Flash memory

PHYSICAL CHARACTERISTICS

Width: 10.37"/263.5 mm
Depth: 19.5"/495.3 mm
Height: 15.5"/393.7 mm
Weight: 50 lbs./22.7 kg

MEDIA SPECIFICATIONS

Label and liner width:
0.79"/20 mm to 4.5"/114 mm

RIBBON WIDTH:

0.79"/20 mm to 4.33"/110 mm

*Specifications listed are for base model printers with standard features only unless otherwise noted. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved.

STANDARD FEATURES

Print methods: Thermal transfer and direct thermal
Construction: 12-gauge steel frame
16 MB SDRAM; 4 MB non-volatile Flash memory
ZebraLink™ connectivity
Single 32 bit 133 Mhz RISC processor
Advanced counters
Early warning system—indicates when to service printhead or change ribbons/media
300 unique darkness settings for print quality
USB 2.0 port for faster connectivity and throughput (plug and play)
Serial and parallel ports
Multilingual backlit LCD control panel
PCMCIA socket
CompactFlash socket
Transmissive and reflective media sensors
Multi-level Element Energy Equalizer (E3™) for superior print quality
Zebra printer driver for Win 95, Win 98, NT 2000

Programming Language

ZPL® II — Universal language for Zebra printers. Simplifies label formatting and enables format compatibility with other Zebra printers.
ZBI™ — Controls and interprets text and data from peripherals and non-ZPL printer programming languages. Transmits captured data over LAN, WAN, or wireless network via e-mail or TCP/IP messaging.

OPERATING CHARACTERISTICS

Environment

Operating Temp (tt): 41° F/5° C to 104° F/40° C
Operating Temp (dt): 32° F/0° C to 104° F/40° C
Storage/Transport Environ. -40° F/-40° C to 140° F/60° C
Operating Humidity 20-85% non-condensing
Storage Humidity 5-85% non-condensing

Electrical

Universal power supply with power-factor correction 90-264 VAC; 48-62 Hz

Communication Interface Capabilities

USB 2.0 port (480 M bits/second)
RS-232C/422/485 multi-drop
Hi-speed, bi-directional, IEEE 1284 parallel interface
ZebraNet® PrinterServer II (optional)
ZebraNet Wireless Card Socket (optional)

Agency Approvals

Bi-National UL 60950 3rd edition/CSA CAN/CSA-C22.2 No. 60950-00 Third Edition; IEC 950/EN60950:1992 w/amendments 1 thru 4 (CB Scheme); EN55022: 1998 Class B; EN55024: 1998; EN61000-3-2,3 w/amendment A12; Canadian ICES-003, Class B; FCC Class B; Argentina 92/98 Phase 3; Australia AS/NZS 3548; R.O.C. CNS 13438

MEDIA CHARACTERISTICS

Labels

Max. Roll Size: 8"/203 mm O.D. on a 3"/76 mm I.D. core
Thickness (label & liner): 0.003"/0.076 mm to 0.012"/0.305 mm

Media Types

Continuous, die-cut or black mark
For optimum print quality and print engine performance, use Genuine Zebra supplies.

Ribbons

Ribbon is recommended to be at least as wide as media.
Max. Roll Size: 3.2"/81.3 mm O.D. on a 1"/25.4 mm I.D. core
Standard Lengths: 1476'/450 m to 984'/300 m; provides 3:1 and 2:1 media roll to ribbon ratios
Ribbon Setup: Ribbon wound ink side out

FONTS/GRAPHICS/SYMBOLOLOGIES

Fonts and Character Sets

Bitmap fonts A through H and GS symbols are expandable up to 10 times, height and width independent
Smooth scalable font O (CG Trimvirate™ Bold Condensed) is expandable dot-by-dot, height and width independent
Sets: IBM Code Page 850 International Characters

Graphic Features

Supports user-defined fonts and graphics— including custom logos

Bar Code Symbolologies

Linear Bar Codes: Code 11, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case Codes, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2- of 5-digit extensions, Plessey; Postnet, Standard 2 of 5, Industrial 2 of 5, Interleaved 2 of 5, LOGMARS, MSI, Codabar and Planet code
2-Dimensional: Codablock, PDF-417, Code 49, Data Matrix, Maxi Code, QR Code TLC 39, and RSS code

OPTIONS AND ACCESSORIES

ZebraNet PrintServer II
ZebraNet Wireless Card Socket
Rewind
Cutter
Bi-fold media door with clear panel
Label peel
Media supply spindle for 40 mm cores
Scalable and international fonts
PC cards
CompactFlash (CF) card
Applicator interface
IBM twinax interface
IBM coax interface
BAR-ONE® software



HEADQUARTERS

Zebra Technologies International, LLC **PHONE:** +1 847.793.2600 or +1 800.423.0442 **FAX:** +1 847.913.8766
ADDRESS: 333 Corporate Woods Parkway, Vernon Hills, IL 60061-3109 U.S.A. **WEB:** www.zebra.com

OTHER LOCATIONS

USA: California, Florida, Rhode Island, Wisconsin **EUROPE:** Denmark, France, Germany, Italy, United Kingdom
ASIA-PACIFIC: Australia, China, Japan, Singapore, South Korea **LATIN AMERICA:** Argentina, Brazil
MIDDLE EAST: United Arab Emirates



An ISO 9001 registered company
©2003 ZIH Corp.
Printed in U.S.A.
#13186L Rev.x (4/03) xM

Barcodes Inc. is a leading provider of barcode, mobile computing and RFID solutions. Headquartered in Chicago, we have been in business since 1994. We have experienced rapid growth every year, thanks to our focus on the customer and our flexible, solution-oriented approach to our customers' needs. We are product experts with deep experience in field mobility, healthcare, retail and warehouse application solutions. We proudly work with over two-thirds of the Fortune 500 list as well as thousands of small and medium-sized businesses.



Dedicated Account Team

A typical Account Team consists of an Account Manager, an onsite Systems Integrator, plus technical resources in specialty areas like Enterprise Mobility, POS systems or Wireless equipment. An Account Manager is the Primary Point of Contact for your business. Your Account Manager makes it a priority to get to know you, your company and all your needs.



Technical Advice and Solution Expertise

We have deep experience installing and supporting data collection and mobility systems for clients in multiple industries and in government. Our Account Managers are industry experts with superior experience in project management. They work hard to understand your business so they can work with our technical experts to make effective recommendations. They will see your project through from the initial solution to implementation and beyond.



Logistical Excellence

Priority orders are completed within minutes and ship the same day. 99.9% of all orders ship on time. We utilize a network of warehouses across the U.S. to ensure that you get what you need, when you need it.



Online resources

Our online resources are intended to make your job easy. We offer secure online ordering, detailed product information, industry news, specials, chat and account management tools, so you can always get the information you need.



Incredible Value and the Broadest Product Offering Available

Our purchasing power means big savings for you. In addition, we are an authorized value-added reseller for all of the trusted manufacturers in the industry and a premier partner of all of the top brands. This access allows us to offer the broadest product offering, excellent prices and the product support you deserve.

CALL US 1.800.351.9962

VISIT US ONLINE
www.barcodesinc.com

Barcodes, Inc, 218 S Wabash Avenue, Suite 500, Chicago IL 60604
Phone 800.351.9962 Fax 312.212.1800 www.barcodesinc.com